

General Configuration Profile				
	Tag	Description	Example	Default Value
1)	[Template Name]	Description that appears in the setup wizard	[Teacher] or [B-Wing Teacher] or [Room 212 Lab]	
2)	softwareini=	Full UNC path to software ini for profile	\\My_school_server\deploy\Student\install.ini	
3)	updateini=	Path to updates folder, leave this one alone	\\007src\Imaging\Updates\updates.ini	
4)	printerini=	Full UNC path to printer ini for profile	\\My_school_server\deploy\Student\printers.ini	
5)	regeditini=	Full UNC path to registry ini for profile	\\My_school_server\deploy\Student\lockdowns.ini	
6)	accountini=	Full UNC path to account ini for profile *	\\My_school_server\deploy\Student\labaccount.ini	
7)	shortcutini=	Full UNC path to shortcut ini for profile	\\My_school_server\deploy\Student\shortcuts.ini	
8)	biospwd=	Setup password to put in the BIOS	SetupPassw0rd	
9)	Join=	Workgroup or Domain	Domain	
10)	DomWGNAME=	Domain or Workgroup to use	mnps	
11)	DomUsername=	Username to use when attaching to domain	mnps	
12)	DomPassword=	Password to use when attaching to domain	JoinPassw0rd	
13)	HomePage=	The IE homepage for the default user *	http://www.google.com/	
14)	Background=	The background image for the default user *	"C:\Program Files\Setup Wizard\Config\Student\NewStudentLogo.bmp"	
15)	Bkgorientation=	How the background image will be displayed	0 = Centered 1 = Stretched 2 = Tiled	
16)	SystemFiles=	Location of zipped files to add to system ‡	\\My_school_server\deploy\Student\files\	
17)	HorzRes=	Horizontal screen resolution	1024	Max
18)	VertRes=	Vertical screen resolution	768	Max

* Local accounts and backgrounds won't have any affect on domain computers. Setting a homepage will affect computers attached to MNPS domain, but not student forest.

‡ The Wizard will unzip all files in this directory to the root of the C: drive. This allows you to add files and directories anywhere on the drive by specially creating your zip files with the "Save Full Path" option selected. Files are extracted after software installations are completed.

Software INI				
	Tag	Description	Example	Default Value
1)	[Unique ID]	A unique ID for the program	[PowerDVD]	
2)	ProgTitle=	The title displayed in the status/log	"Power DVD 7.0"	
3)	instfile=	Full path to installer executable or MSI *	"C:\Program Files\Setup Wizard\software\abtcsetup5.msi"	
4)	silentarg=	Optional argument for the instfile*	"ALLUSERS=1 PASSWORD=ABTutorPassword"	
5)	postinst=	Optional program to run after the instfile ‡	"C:\Program Files\Setup Wizard\software\abt5Settings.exe"	
6)	postinstargs=	Optional argument for the postinst ‡	/S	
7)	form=	Optional form factor requirement †	0 = None 1 = Only install to Laptops 2 = Only install to Desktops	0
8)	CDRW=	Optional CD writer requirement †	0 = None 1 = Only install to computers with a CDRW drive	0
9)	DVD=	Optional DVD reader requirement †	0 = None 1 = Only install to computers with a DVDdrive	0
10)	Territory=	Optional territory requirement †	0 = None 1-7 = Only install if matching territory code retrieved	0
11)	LocCode=	Optional location requirement †	0 = None ### = Only install if matching location code retrieved	0
12)	Level=	Optional grade level Requirement †	0 = None 1 = ES 2 = MS 3 = HS 4 = ALC	0

* The instfile argument is the required name of the main install executable. The silentarg is optional and can be anything that is to be passed to the instfile at runtime.

‡ The postinst argument works the same as the instfile argument. It is a program or MSI that would be executed after the instfile has run.

† The requirement arguments allow you to apply some logic at the time of install. Instead of having to create a profile for every situation, you can specify that a program should only be installed if the computer meets certain criteria. An obvious example is that the DVD software only installs if there is a DVD drive attached to the computer. By setting the argument to '0' or leaving it blank, the Wizard skips the requirement. If you need to match two criteria for one install, you'll need to create two instances of the installer in the INF. For instance if you wanto have the same program install at high schools and middle schools, but not elementary schools, you will need to create to instances of the same installer and set one to Level=2 and the other to Level=3. If you do this, be sure to give each instance a different [Unique ID] or the Wizard will skip them both!

Printer INI				
	Tag	Description	Example	Default Value
1)	[Name]	A unique name for the printer	[B-Wing Laser Printer]	
2)	Location=	Optional location for of the printer	"Teachers Lounge"	
3)	Hostname=	Hostname or IP of the printer	999PTLXRMNUM	
4)	Portname=	Name of the port	999PTLXRMNUM	
5)	DriverDir=	Full path to printer driver directory	\\007src\Imaging\PrintDrivers\LXT640\ (double backslash is important)	
6)	DriverINF=	Name of driver INF	LMAAT2DA.INF	
7)	DriverName=	Name of printer driver from INF	"Lexmark T640" (must match the name in the DriverINF file)	

Regedit INI				
	Tag	Description	Example	Default Value
1)	[Name]	A unique name for the edit	[Logon_NoLastUser]	
2)	operation=	Operation to perform [write delete]	write	
3)	key=	Registry key to edit*	HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows	
4)	valuenam=	Value name in the key to change	dontdisplaylastusername	
5)	valuetype=	Value type [REG_DWORD REG_SZ etc]	REG_DWORD	
6)	value=	Value to assign	"00000001"	
* The setup Wizard will mount the default user registry hive prior to installing the registry changes. To make changes to the Default user hive the key must start with 'HKEY_USERS\Default User'. Making changes to HKEY_Current_User will only affect the local admin account, but edits pointed to 'HKEY_USERS\Default User' will affect any account created after the Setup Wizard completes. Edits made to HKEY_Local_Machine will of course affect every account on the system.				

Account INI				
	Tag	Description	Example	Default Value
1)	[Name]	Description of account	[Student User]	
2)	username=	Username of account	student	
3)	password=	Password for account	student	
4)	group=	Group to put user in	Users	
5)	script=	Full path to login script (copied locally)	C:\Program Files\Setup Wizard\Config\Student\desklock.exe	

Shortcut INI				
	Tag	Description	Example	Default Value
1)	[Name]	a unique name for the task	[Shortcut1]	
2)	Location=	Where to put the shortcut [desktop menu] *	desktop	
3)	Filename=	Full filename of the link *	"Shortcut test.LNK"	
4)	Exe=	Location of executable	C:\windows\bginfo.exe	
* The location argument specifies whether the shortcut will be placed in Documents and Settings\All Users\Desktop or Documents and Settings\All Users\Start Menu. To place into a subfolder of either of those locations, add it to the beginning of the filename argument. For instance to add a shortcut to the all users programs menu, specify 'desktop' for location and 'Programs\shortcut.LNK' as the filename.				

Email INI*				
	Tag	Description	Example	Default Value
1)	[Name]	A unique name for the task	[Default]	
2)	SMTPAddr=	SMTP address	smtp.k12tn.ne	smtp.server.net
3)	FromName=	Name of sender	Danny California	Computer Name
4)	FromAddr=	Address of sender	danny.california@mnps.org	techdispatch@server.org
5)	ToAddr=	Address of recipient	recipient@mnps.org	helpdesk@server.org
* The Setup Wizard will automatically create an email containing the details of the setup events. A file called mailconfig.ini must be present in the folder where config.ini is located.				